

Coming Soon



FEATURES

- 80 PLUS Platinum
- Cold Redundancy
- Smart Ride Through
- Black Box Recorder
- Active Power Factor Correction
- Closed Loop System Protection (CLST)
- Support PMBus 1.2
- Internal OR'ing
- N+1 Redundant

CDR-9211-2M1

- Dimension : 346 x 76 x 40 mm (D x W x H)
- Total Max Power : 920W



UL , cUL , TUV , CE , CCC , BSMI , CB , FCC class A , CISPR Class A , RoHS

INPUT SPECIFICATIONS	
Input voltage	AC input 90 - 264Vac / DC input 180 - 300Vdc
Input frequency	47 - 63Hz
Input current	100 - 240Vac / 11.4 - 3.9A 200 - 240Vdc / 5.6 - 3.4A

GENERAL SPECIFICATIONS	
Hold-up time	11 ms @ 75% Load
Efficiency	at least 94% @ 50% load
MTBF	At 30 degrees Celsius, with normal operation at least 400,000hours.

ENVIRONMENTAL SPECIFICATIONS	
Temperature	Operating temperature range: 50 degrees Celsius maximum Non-operating Ambient: -40°C to +70°C,
Altitude	Operating: to 16,500 feet (5,000 meters) Non-operating: to 35,000 feet (10,580 meters)
Relative humidity	Operating : 5% to 90% RH, Non-condensing Storage : 5% to 95% RH, Non-condensing

OUTPUT SPECIFICATIONS		
Voltage	+12V	+5Vsb
Regulation	±5%	±5%
Max Load	75A (100-240Vac) (200-240Vdc)	4.0A
Ripple & Noise	120mVp-p	50mVp-p

